The Original Metal Studded Rubber Flooring

Installation Instructions:

• Floor must be clean and smooth. Remove any old floor covering and be sure the sub-floor is free of all residue.

♦ Install quality white shield felt or saturated paper with multi-purpose adhesive. (This is used to allow for easier tile removal should that be required).

◆ Allow to dry thoroughly.

♦ Use a two part epoxy with a 1/8" x 1/8" square notched trowel. Spread adhesive and install tiles with smooth side up. Roll with heavy floor tile roller.

♦ For ease of cutting tile along walls, remove studs closest to cutting line. Pull studs out from back as one would remove a thumb tack.

 Punched-out material or waste material from holes is available upon request to plug holes where desired.

Maintenance:

• Sweep and Wash floor with a mild detergent and water solution. Floor must be dried with a soft cloth. Never leave floor wet. The floor can be waxed if desired but the shine achieved by buffing is better and longer lasting.

Product Specification:

- ♦ Each tile is 12" x 12" x 1/8" solid rubber.
- Tiles contain 144 studs; one every square inch.

• Studs are inserted through the back of the tile so that the face is smooth surface combination of metal studs and tile.

♦ ASTM F 1344 specification for rubber floor tile. Class I, Type A. Federal Specification SS-T 312-B, Type III (Note: Specifications are based on manufacturer's test results.) For complete data please visit the following URL address:

http://thematking.com/business_industry/architectural/flooring/elevator-flooring/metalstudded/tech-sheets/TECHNICAL-DATA.pdf

> THE MAT KING is a d/b/a of Geoffrey Drew Marketing, Inc. 740 West End Avenue; Suite 1 New York, NY 10025 USA Phone: 646-998-4208 or Phone: 800-442-6544 Fax: 646-998-4073 or Fax: 800-Mats-Fax (628-7329)

www.thematking.com information@thematking.com