

3

Nomad™

Printed Carpet Matting 6600

1.0 Product Description

The product shall be a tufted loop pile carpet entry mat for medium traffic applications. The mat features a straight line design utilizing two different sizes of nylon 66 fibers. Rows of large diameter fibers are combined with rows of small diameter fibers. This arrangement of fibers improves dirt and water pick up and holding performance. The mat is designed with a slip-resistant vinyl backing which helps hold dirt and water within the mat until the mat is cleaned.

2.0 Intended Use

For use in medium traffic building entrances where snow, water and/or dirt tracking is a problem.

3.0 Standard Sizes

Actual (Nominal) Widths: 34 in. (3 ft.), 46 in. (4 ft.) or 70 in. (6 ft.)
Lengths*: 2 ft. to 60 ft. in 1-foot increments

*Length Tolerances: Lengths may be 2 inches shorter than stated.

4.0 Images and Colors

Virtually any image in a palette of 70 standard colors. Custom colors are available. Provide colors for custom color matching. Almost any color or color combinations can be used; however, we cannot guarantee exact color matching.

5.0 Requirements

Detailed Requirements:

<u>Property</u>	<u>Typical Values</u>
Thickness ASTM D-418	0.3 inches (7.6 mm)
Weight ASTM D-418	5.8 lb./yd.2 (3.1 kg/m2)
Flammability	
DOC FF 1-70 (Pill Test)	Passes

The product shall be made of two different sizes of nylon 66 fibers featuring a loop pile tufted structure and straight line design. Rows of large diameter fibers arranged between rows of fine diameter fibers provide excellent dirt and water removal. The product has a slip-resistant, vinyl backing and edging on all four sides.

6.0 Packaging and Marking

One mat per carton. Each carton shall be marked with product name and manufacturer's trade name.

7.0 Cleaning and Maintenance

Daily Maintenance

Vacuum daily.

Use an upright beater-brush dry vacuum adjusted to its most powerful setting. Move nozzle slowly over mat to allow time for dirt to be picked up.

In heavier traffic areas or at pivot points, rotate matting end for end when repositioning.

Important: Keeping the backing of the mat clean is critical in minimizing the mat "walking". Floor under mat must also be kept clean (swept and/or damp mopped underneath mat).

Weekly Maintenance:

1. Remove matting from service.
2. Turn matting over and run beater bar, dry vacuum on back side of matting.
3. Pick up matting.
4. Clean up dirt/debris from floor (sweep, vacuum, damp mop, etc.)
5. Place matting back in service and vacuum top surface of matting.

Wet Conditions for Mats and Rolls:

1. Use an extractor or wet vacuum to remove as much water as possible from mat.
2. Allow mat to dry. Hang up if necessary. Use of fan or blower will reduce dry time.

Restorative Maintenance:

Frequency of restorative maintenance will depend on the amount of traffic and soil in the area of application.

Rotary Shampoo and Extract

1. Wet matting with diluted solution of 3M™ Carpet Pretreatment or 3M™ Carpet Extraction Cleaner.
2. Loosen dirt using a rotary brush.
3. Extract at least two times. (If heavily soiled, repeating this procedure may be required.)
4. Let mat dry.

OR

High Pressure Washer

Use high pressure washer (i.e., at self-service car wash).

1. Hang mat up.
2. Wash mat thoroughly.
3. Rinse mat thoroughly.
4. Let mat dry.

3M Branch Sales Offices

ANCHORAGE

11151 Calaska Circle
Anchorage, AK 99515
Telephone: 907/522-5200
Facsimile: 907/522-1645

CONTINENTAL UNITED STATES

Customer Service Department
3M Center Building 223-5N-07
St. Paul, MN 55144-1000
Order Entry 1-800-852-9722
Facsimile: 1-800-447-0408

HONOLULU

4443 Malaai Street
Honolulu, HI 96818
Mail to: P.O. Box 30048
Honolulu, HI 96820
Telephone: 808/422-2721
Facsimile: 808/422-9557

3M CANADA

1840 Oxford Street East
London, Ontario, Canada
N5V 3G2
Mail to: P.O. Box 5757
London, Ontario, Canada
N6A 4T1
Telephone: 800/364-3577
Facsimile: 800/479-4453

Important Notice:

This flyer is intended to be an introductory summary. The information provided is based upon typical conditions and is believed to be reliable; however, due to the wide variety of intervening factors 3M does not warrant that the results will necessarily be obtained. All details concerning product specifications and terms of sale are available from 3M.

3

Commercial Care Division

3M Center
St. Paul, MN 55144-1000

3M and Nomad are trademarks of 3M.
Copyright © 2001, 3M IPC. All rights reserved.
70-0710-3534-2 Rev. A